



BNF (給油式、めねじタイプ)

BNF-□□
BNF-□□L



材質



- ①ハウジング：S35C亜鉛メッキ
- ②インサート：銅合金
- ③ボール：SUJ2 HRC58以上
- ニップル付

品 番	価 格	主要寸法														最小静破壊 ラジアル 荷重(kg f)	限界荷重(kg f)		重量 (g)
		B	W	G	O	D	F	H	A	K	X	J	L	E	M		ラジアル 荷重	アキシャル 荷重	
BNF- 5(L)	1,000	5	8	6	7.71	16	27	35	12	11	9	9	4	11.11	M5×0.8	930	620	230	18
BNF- 6(L)	1,030	6	9	6.7	8.96	18	30	39	14	13	11	10	5	12.70	M6×1	1,040	690	270	26
BNF- 8(L)	1,110	8	12	9	10.40	22	36	47	17	16	14	12.5	5	15.88	M8×1.25	1,490	990	430	46
BNF-10(L)	1,290	10	14	11	12.92	26	43	56	21	19	17	15	6.5	19.05	M10×1.5	2,010	1,340	630	74
BNF-12(L)	1,510	12	16	12	15.43	30	50	65	24	22	19	17.5	6.5	22.23	M12×1.75	2,470	1,650	800	113
BNF-14(L)	1,810	14	19	14	16.86	34	57	74	27	25	22	20	8	25.40	M14×2	3,130	2,090	1,070	166
BNF-16(L)	2,380	16	21	15	19.39	38	64	83	33	27	22	22	8	28.58	M16×2	3,700	2,470	1,290	202
BNF-18(L)	2,910	18	23	17	21.89	42	71	92	36	31	27	25	10	31.75	M18×1.5	4,490	2,990	1,620	296
BNF-20(L)	3,460	20	25	18	24.38	46	77	100	40	34	30	27.5	10	34.93	M20×1.5	5,180	3,460	1,890	364
BNF-22(L)	4,130	22	28	20	25.84	50	84	109	43	37	32	30	12	38.10	M22×1.5	6,100	4,070	2,290	480
BNF-25(L)	注)5,490	25	31	22	29.60	56	94	122	48	42	36	33.5	12	42.86	M24×2	7,420	4,950	2,830	673
BNF-30(L)	注)7,300	30	37	26	34.81	67	110	143.5	56	50	41	40	15	50.80	M30×2	11,000	7,370	3,960	1,050

※左ネジの場合はLを品番の次に追記してください。
注) ロット受注生産につき別途お問い合わせください。

BNM (給油式、おねじタイプ)

BNM-□□
BNM-□□L



材質


- ①ハウジング：S35C亜鉛メッキ
- ②インサート：銅合金
- ③ボール：SUJ2 HRC58以上
- ニップル付

品 番	価 格	主要寸法										最小静破壊 ラジアル 荷重(kg f)	限界荷重(kg f)		重量 (g)
		B	W	G	O	D	F	H	A	E	M		ラジアル 荷重	アキシャル 荷重	
BNM- 5(L)	930	5	8	6	7.71	16	33	41	20	11.11	M5×0.8	930	620	230	14
BNM- 6(L)	980	6	9	6.7	8.96	18	36	45	22	12.70	M6×1	1,040	690	270	19
BNM- 8(L)	1,020	8	12	9	10.40	22	42	53	25	15.88	M8×1.25	1,490	990	430	35
BNM-10(L)	1,180	10	14	11	12.92	26	48	61	29	19.05	M10×1.5	2,010	1,340	630	61
BNM-12(L)	1,350	12	16	12	15.43	30	54	69	33	22.23	M12×1.75	2,470	1,650	800	92
BNM-14(L)	1,640	14	19	14	16.86	34	60	77	36	25.40	M14×2	3,130	2,090	1,070	131
BNM-16(L)	2,190	16	21	15	19.39	38	66	85	40	28.58	M16×2	3,700	2,470	1,290	184
BNM-18(L)	2,700	18	23	17	21.89	42	72	93	44	31.75	M18×1.5	4,490	2,990	1,620	268
BNM-20(L)	3,080	20	25	18	24.38	46	78	101	47	34.93	M20×1.5	5,180	3,460	1,890	330
BNM-22(L)	3,780	22	28	20	25.84	50	84	109	51	38.10	M22×1.5	6,100	4,070	2,290	438
BNM-25(L)	注)4,950	25	31	22	29.60	56	94	122	57	42.86	M24×2	7,420	4,950	2,830	575
BNM-30(L)	注)7,110	30	37	26	34.81	67	110	143.5	66	50.80	M30×2	11,000	7,370	3,960	996

※左ネジの場合はLを品番の次に追記してください。
注) ロット受注生産につき別途お問い合わせください。

DF (無給油式、めねじタイプ)

DF-□□
DF-□□L



材質


- ①ハウジング：S35C亜鉛メッキ
- ②インサート：テフロン
- ③ボール：SUJ2 HRC58以上

品 番	価 格	主要寸法															許容 傾斜角 α2	限界荷重(kg f)		重量 (g)
		B	W	G	O	D	F	H	A	K	X	J	L	E	M	P		ラジアル 荷重	アキシャル 荷重	
DF- 5(L)	1,000	5	8	6	7.71	16	27	35	12	11	9	9	4	11.11	M5×0.8	3	12	590	230	18
DF- 6(L)	1,030	6	9	6.7	8.96	18	30	39	14	13	11	10	5	12.70	M6×1	3.3	11	650	250	26
DF- 8(L)	1,110	8	12	9	10.40	22	36	47	17	16	14	12.5	5	15.88	M8×1.25	4.5	12	800	300	45
DF-10(L)	1,290	10	14	11	12.92	26	43	56	21	19	17	15	6.5	19.05	M10×1.5	5.5	12	1,050	390	76
DF-12(L)	1,510	12	16	12	15.43	30	50	65	24	22	19	17.5	6.5	22.23	M12×1.75	6	13	1,300	500	114
DF-14(L)	1,810	14	19	14	16.86	34	57	74	27	25	22	20	8	25.40	M14×2	7	14	1,700	650	158
DF-16(L)	2,380	16	21	15	19.39	38	64	83	33	27	22	22	8	28.58	M16×2	7.5	14	2,100	800	200
DF-18(L)	2,910	18	23	17	21.89	42	71	92	36	31	27	25	10	31.75	M18×1.5	8.5	14	2,550	950	288
DF-20(L)	3,460	20	25	18	24.38	46	77	100	40	34	30	27.5	10	34.93	M20×1.5	9	14	3,000	1,100	372
DF-22(L)	4,130	22	28	20	25.84	50	84	109	43	37	32	30	12	38.10	M22×1.5	10	15	3,550	1,350	475
DF-25(L)	注)5,490	25	31	22	29.60	56	94	122	48	42	36	33.5	12	42.86	M24×2	11	15	4,500	2,830	673
DF-30(L)	注)7,300	30	37	26	34.80	67	110	143.5	56	50	41	40	15	50.80	M30×2	13	15	7,000	3,960	1,050

※左ネジの場合はLを品番の次に追記してください。
注)ロット受注生産につき別途お問い合わせください。

DM (無給油式、おねじタイプ)

DM-□□
DM-□□L



材質

- ①ハウジング：S35C亜鉛メッキ
- ②インサート：テフロン
- ③ボール：SUJ2 HRC58以上


品 番	価 格	主要寸法												許容 傾斜角 α2	限界荷重(kg f)		重量 (g)
		B	W	G	O	D	F	H	A	E	M	P	ラジアル 荷重		アキシャル 荷重		
DM- 5 (L)	930	5	8	6	7.71	16	33	41	20	11.11	M5×0.8	3	12	590	230	14	
DM- 6 (L)	980	6	9	6.7	8.96	18	36	45	22	12.70	M6×1	3.3	11	650	250	19	
DM- 8 (L)	1,020	8	12	9	10.40	22	42	53	25	15.88	M8×1.25	4.5	12	800	300	36	
DM-10 (L)	1,180	10	14	11	12.92	26	48	61	29	19.05	M10×1.5	5.5	12	1,050	390	60	
DM-12 (L)	1,350	12	16	12	15.43	30	54	69	33	22.23	M12×1.75	6	13	1,300	500	89	
DM-14 (L)	1,640	14	19	14	16.86	34	60	77	36	25.40	M14×2	7	14	1,700	650	129	
DM-16 (L)	2,190	16	21	15	19.39	38	66	85	40	28.58	M16×2	7.5	14	2,100	800	181	
DM-18 (L)	2,700	18	23	17	21.89	42	72	93	44	31.75	M18×1.5	8.5	14	2,550	950	250	
DM-20 (L)	3,080	20	25	18	24.38	46	78	101	47	34.93	M20×1.5	9	14	3,000	1,100	333	
DM-22 (L)	3,780	22	28	20	25.84	50	84	109	51	38.10	M22×1.5	10	15	3,550	1,350	430	
DM-25 (L)	注)4,950	25	31	22	29.60	56	94	122	57	42.86	M24×2	11	15	4,500	2,830	575	
DM-30 (L)	注)7,110	30	37	26	34.80	67	110	143.5	66	50.80	M30×2	13	15	7,000	3,960	996	

※左ネジの場合はLを品番の次に追記してください。
注)ロット受注生産につき別途お問い合わせください。

SDF (無給油式、めねじタイプ)

ステンレス

SDF-□□
SDF-□□L



材質

- ①ハウジング : SUS303
- ②インサート : テフロン
- ③ボール : SUS440C HRC58以上


品 番	価格	主要寸法														許容 傾斜角 α2	限界荷重 (kg f)		重量 (g)	
		B	W	G	O	D	F	H	A	K	X	J	L	E	M		P	ラジアル 荷重		アキシャル 荷重
SDF- 5 (L)	2,470	5	8	6	7.71	16	27	35	12	11	9	9	4	11.11	M5×0.8	3	12	590	230	18
SDF- 6 (L)	2,530	6	9	6.7	8.96	18	30	39	14	13	11	10	5	12.70	M6×1	3.3	11	650	250	26
SDF- 8 (L)	2,970	8	12	9	10.40	22	36	47	17	16	14	12.5	5	15.88	M8×1.25	4.5	12	800	300	45
SDF-10 (L)	3,570	10	14	11	12.92	26	43	56	21	19	17	15	6.5	19.05	M10×1.5	5.5	12	1,050	390	76
SDF-12 (L)	4,370	12	16	12	15.43	30	50	65	24	22	19	17.5	6.5	22.23	M12×1.75	6	13	1,300	500	114
SDF-14 (L)	5,600	14	19	14	16.86	34	57	74	27	25	22	20	8	25.40	M14×2	7	14	1,700	650	158
SDF-16 (L)	6,930	16	21	15	19.39	38	64	83	33	27	22	22	8	28.58	M16×2	7.5	14	2,100	800	200
SDF-18 (L)	9,430	18	23	17	21.89	42	71	92	36	31	27	25	10	31.75	M18×1.5	8.5	14	2,550	950	288
SDF-20 (L)	11,400	20	25	18	24.38	46	77	100	40	34	30	27.5	10	34.93	M20×1.5	9	14	3,000	1,100	372
SDF-22 (L)	12,600	22	28	20	25.84	50	84	109	43	37	32	30	12	38.10	M22×1.5	10	15	3,550	1,350	475
SDF-25 (L)	17,100	25	31	22	29.60	56	94	122	48	42	36	33.5	12	42.86	M24×2	11	15	4,500	2,830	673
SDF-30 (L)	21,100	30	37	26	34.80	67	110	143.5	56	50	41	40	15	50.80	M30×2	13	15	7,000	3,960	1,050

※左ネジの場合はLを品番の次に追記してください。

SDM (無給油式、おねじタイプ)

ステンレス

SDM-□□
SDM-□□L



材質

- ①ハウジング : SUS303
- ②インサート : テフロン
- ③ボール : SUS440C HRC58以上

品 番	価格	主要寸法											許容 傾斜角 α2	限界荷重 (kg f)		重量 (g)
		B	W	G	O	D	F	H	A	E	M	P		ラジアル 荷重	アキシャル 荷重	
SDM- 5 (L)	2,330	5	8	6	7.71	16	33	41	20	11.11	M5×0.8	3	12	590	230	14
SDM- 6 (L)	2,400	6	9	6.7	8.96	18	36	45	22	12.70	M6×1	3.3	11	650	250	19
SDM- 8 (L)	2,870	8	12	9	10.40	22	42	53	25	15.88	M8×1.25	4.5	12	800	300	36
SDM-10 (L)	3,430	10	14	11	12.92	26	48	61	29	19.05	M10×1.5	5.5	12	1,050	390	60
SDM-12 (L)	4,200	12	16	12	15.43	30	54	69	33	22.23	M12×1.75	6	13	1,300	500	89
SDM-14 (L)	5,470	14	19	14	16.86	34	60	77	36	25.40	M14×2	7	14	1,700	650	129
SDM-16 (L)	6,800	16	21	15	19.39	38	66	85	40	28.58	M16×2	7.5	14	2,100	800	181
SDM-18 (L)	9,270	18	23	17	21.89	42	72	93	44	31.75	M18×1.5	8.5	14	2,550	950	250
SDM-20 (L)	11,200	20	25	18	24.38	46	78	101	47	34.93	M20×1.5	9	14	3,000	1,100	333
SDM-22 (L)	12,100	22	28	20	25.84	50	84	109	51	38.10	M22×1.5	10	15	3,550	1,350	430
SDM-25 (L)	16,900	25	31	22	29.60	56	94	122	57	42.86	M24×2	11	15	4,500	2,830	575
SDM-30 (L)	20,800	30	37	26	34.80	67	110	143.5	66	50.80	M30×2	13	15	7,000	3,960	996

※左ネジの場合はLを品番の次に追記してください。