





※黒染処理は施していません



形状：RB



形状：B

共通仕様

- 精度等級：JISN8級
(旧JIS4級)
- 歯形：並歯
- 圧力角：20°
- 材料：S45C相当


● M1

品番	TDK価格	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB1-15	560	15	RB	15	17	17	10	20	30	6	0.039
MSB1-16	580	16	RB	16	18	18	10	20	30	6	0.045
MSB1-17	600	17	RB	17	19	19	10	20	30	6	0.051
MSB1-18	620	18	RB	18	20	20	10	20	30	6	0.059
MSB1-19	630	19	RB	19	21	21	10	20	30	6	0.068
MSB1-20	640	20	B	20	22	16	10	10	20	6	0.035
MSB1-21	650	21	B	21	23	17	10	10	20	6	0.038
MSB1-22	670	22	B	22	24	18	10	10	20	6	0.044
MSB1-23	670	23	B	23	25	18	10	10	20	6	0.047
MSB1-24	680	24	B	24	26	20	10	10	20	6	0.054
MSB1-25	680	25	B	25	27	20	10	10	20	6	0.057
MSB1-26	720	26	B	26	28	22	10	10	20	6	0.066
MSB1-27	720	27	B	27	29	22	10	10	20	6	0.07
MSB1-28	730	28	B	28	30	22	10	10	20	6	0.072
MSB1-29	750	29	B	29	31	24	10	10	20	6	0.082
MSB1-30	760	30	B	30	32	25	10	10	20	8	0.084
MSB1-32	750	32	B	32	34	26	10	10	20	8	0.094
MSB1-34	810	34	B	34	36	26	10	10	20	8	0.12
MSB1-35	820	35	B	35	37	26	10	10	20	8	0.125
MSB1-36	850	36	B	36	38	28	10	10	20	8	0.13
MSB1-38	930	38	B	38	40	32	10	10	20	8	0.14
MSB1-40	970	40	B	40	42	35	10	10	20	8	0.16
MSB1-42	1,010	42	B	42	44	35	10	10	20	8	0.17
MSB1-44	1,080	44	B	44	46	35	10	10	20	8	0.18
MSB1-45	1,100	45	B	45	47	35	10	10	20	8	0.19
MSB1-46	1,110	46	B	46	48	35	10	10	20	8	0.2
MSB1-48	1,210	48	B	48	50	35	10	10	20	8	0.21
MSB1-50	1,240	50	B	50	52	35	10	10	20	8	0.22
MSB1-52	1,250	52	B	52	54	35	10	10	20	8	0.23
MSB1-54	1,360	54	B	54	56	35	10	10	20	8	0.24
MSB1-55	1,370	55	B	55	57	35	10	10	20	8	0.25
MSB1-56	1,380	56	B	56	58	35	10	10	20	8	0.26
MSB1-58	1,530	58	B	58	60	35	10	10	20	8	0.27
MSB1-60	1,530	60	B	60	62	35	10	10	20	8	0.3
MSB1-62	1,670	62	B	62	64	40	10	10	20	8	0.32
MSB1-64	1,690	64	B	64	66	40	10	10	20	8	0.35
MSB1-65	1,730	65	B	65	67	40	10	10	20	8	0.36
MSB1-66	1,750	66	B	66	68	40	10	10	20	8	0.36
MSB1-68	1,880	68	B	68	70	40	10	10	20	8	0.38
MSB1-70	1,900	70	B	70	72	40	10	10	20	8	0.4
MSB1-72	2,060	72	B	72	74	40	10	10	20	8	0.42
MSB1-75	2,100	75	B	75	77	40	10	10	20	8	0.44
MSB1-76	2,160	76	B	76	78	40	10	10	20	8	0.45
MSB1-80	2,290	80	B	80	82	40	10	10	20	8	0.49


※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。



※黒染処理は施していません



形状：RB



形状：B

共通仕様

- 精度等級：JISN8級
(旧JIS4級)
- 歯形：並歯
- 圧力角：20°
- 材料：S45C相当


● M1.5

品番	TDK価格	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB1.5-12	640	12	RB	18	21	21	15	15	30	6	0.06
MSB1.5-13	670	13	RB	19.5	22.5	22.5	15	15	30	6	0.072
MSB1.5-14	670	14	B	21	24	16	15	10	25	6	0.048
MSB1.5-15	680	15	B	22.5	25.5	18	15	10	25	6	0.058
MSB1.5-16	720	16	B	24	27	20	15	10	25	6	0.069
MSB1.5-17	760	17	B	25.5	28.5	21	15	10	25	6	0.078
MSB1.5-18	810	18	B	27	30	22	15	10	25	6	0.088
MSB1.5-19	820	19	B	28.5	31.5	23	15	10	25	6	0.1
MSB1.5-20	840	20	B	30	33	24	15	10	25	6	0.12
MSB1.5-21	810	21	B	31.5	34.5	25	15	10	25	6	0.13
MSB1.5-22	880	22	B	33	36	26	15	10	25	6	0.13
MSB1.5-23	940	23	B	34.5	37.5	27	15	10	25	6	0.15
MSB1.5-24	980	24	B	36	39	28	15	10	25	6	0.17
MSB1.5-25	1,040	25	B	37.5	40.5	30	15	10	25	6	0.19
MSB1.5-26	1,060	26	B	39	42	32	15	10	25	8	0.2
MSB1.5-27	1,100	27	B	40.5	43.5	34	15	10	25	8	0.22
MSB1.5-28	1,120	28	B	42	45	36	15	10	25	8	0.24
MSB1.5-29	1,150	29	B	43.5	46.5	37	15	10	25	8	0.25
MSB1.5-30	1,190	30	B	45	48	38	15	10	25	8	0.27
MSB1.5-32	1,270	32	B	48	51	40	15	10	25	8	0.31
MSB1.5-34	1,330	34	B	51	54	40	15	10	25	8	0.33
MSB1.5-35	1,410	35	B	52.5	55.5	42	15	10	25	8	0.36
MSB1.5-36	1,430	36	B	54	57	45	15	10	25	8	0.39
MSB1.5-38	1,600	38	B	57	60	45	15	10	25	10	0.41
MSB1.5-40	1,620	40	B	60	63	45	15	10	25	10	0.45
MSB1.5-42	1,800	42	B	63	66	45	15	10	25	10	0.48
MSB1.5-44	1,950	44	B	66	69	45	15	10	25	10	0.52
MSB1.5-45	1,970	45	B	67.5	70.5	45	15	10	25	10	0.53
MSB1.5-46	2,050	46	B	69	72	45	15	10	25	10	0.55
MSB1.5-48	2,180	48	B	72	75	45	15	10	25	10	0.59
MSB1.5-50	2,210	50	B	75	78	45	15	10	25	10	0.63
MSB1.5-52	2,370	52	B	78	81	50	15	10	25	13	0.69
MSB1.5-54	2,550	54	B	81	84	50	15	10	25	13	0.74
MSB1.5-55	2,550	55	B	82.5	85.5	50	15	10	25	13	0.76
MSB1.5-56	2,590	56	B	84	87	50	15	10	25	13	0.78
MSB1.5-58	2,770	58	B	87	90	50	15	10	25	13	0.83
MSB1.5-60	2,810	60	B	90	93	50	15	10	25	13	0.88
MSB1.5-62	3,060	62	B	93	96	55	15	10	25	13	0.96
MSB1.5-64	3,380	64	B	96	99	55	15	10	25	13	1.01
MSB1.5-65	3,410	65	B	97.5	100.5	55	15	10	25	13	1.04
MSB1.5-66	3,490	66	B	99	102	55	15	10	25	13	1.07
MSB1.5-68	3,510	68	B	102	105	55	15	10	25	13	1.12
MSB1.5-70	3,540	70	B	105	108	55	15	10	25	13	1.18
MSB1.5-72	3,840	72	B	108	111	55	15	10	25	13	1.24
MSB1.5-75	3,980	75	B	112.5	115.5	60	15	10	25	13	1.38
MSB1.5-76	4,010	76	B	114	117	60	15	10	25	13	1.41
MSB1.5-80	4,370	80	B	120	123	60	15	10	25	13	1.54

※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。



※黒染処理は施していません



形状：B

共通仕様

- 精度等級：JISN8級
(旧JIS4級)
- 歯形：並歯
- 圧力角：20°
- 材料：S45C相当


● M2

品番	TDK価格	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB2-12	770	12	B	24	28	18	20	10	30	8	0.074
MSB2-13	820	13	B	26	30	20	20	10	30	8	0.091
MSB2-14	860	14	B	28	32	20	20	10	30	8	0.11
MSB2-15	900	15	B	30	34	24	20	10	30	10	0.13
MSB2-16	970	16	B	32	36	26	20	10	30	10	0.15
MSB2-17	990	17	B	34	38	28	20	10	30	10	0.17
MSB2-18	1,100	18	B	36	40	30	20	10	30	10	0.2
MSB2-19	1,150	19	B	38	42	31	20	10	30	10	0.22
MSB2-20	1,190	20	B	40	44	32	20	10	30	10	0.24
MSB2-21	1,270	21	B	42	46	34	20	10	30	10	0.27
MSB2-22	1,320	22	B	44	48	36	20	10	30	10	0.3
MSB2-23	1,430	23	B	46	50	37	20	10	30	10	0.33
MSB2-24	1,470	24	B	48	52	38	20	10	30	10	0.36
MSB2-25	1,490	25	B	50	54	40	20	10	30	10	0.39
MSB2-26	1,620	26	B	52	56	42	20	10	30	10	0.43
MSB2-27	1,640	27	B	54	58	45	20	10	30	10	0.47
MSB2-28	1,790	28	B	56	60	45	20	10	30	10	0.49
MSB2-29	1,800	29	B	58	62	47	20	10	30	10	0.53
MSB2-30	1,970	30	B	60	64	50	20	10	30	10	0.58
MSB2-32	2,020	32	B	64	68	50	20	10	30	10	0.64
MSB2-34	2,210	34	B	68	72	50	20	10	30	10	0.71
MSB2-35	2,370	35	B	70	74	52	20	10	30	10	0.75
MSB2-36	2,400	36	B	72	76	55	20	10	30	10	0.81
MSB2-38	2,600	38	B	76	80	55	20	10	30	10	0.88
MSB2-40	2,790	40	B	80	84	55	20	10	30	13	0.95
MSB2-42	2,880	42	B	84	88	55	20	10	30	13	1.03
MSB2-44	3,100	44	B	88	92	55	20	10	30	13	1.12
MSB2-45	3,240	45	B	90	94	55	20	10	30	13	1.16
MSB2-46	3,330	46	B	92	96	55	20	10	30	13	1.21
MSB2-48	3,680	48	B	96	100	55	20	10	30	13	1.3
MSB2-50	3,870	50	B	100	104	55	20	10	30	13	1.4
MSB2-52	4,000	52	B	104	108	55	20	10	30	13	1.5
MSB2-54	4,310	54	B	108	112	55	20	10	30	13	1.6
MSB2-55	4,320	55	B	110	114	55	20	10	30	13	1.66
MSB2-56	4,350	56	B	112	116	55	20	10	30	13	1.71
MSB2-58	5,130	58	B	116	120	60	20	10	30	13	1.86
MSB2-60	5,140	60	B	120	124	60	20	10	30	13	1.99
MSB2-62	5,190	62	B	124	128	60	20	10	30	13	2.1
MSB2-64	5,460	64	B	128	132	60	20	10	30	13	2.22
MSB2-65	5,530	65	B	130	134	60	20	10	30	13	2.28
MSB2-66	5,560	66	B	132	136	60	20	10	30	13	2.35
MSB2-68	6,180	68	B	136	140	60	20	10	30	13	2.48
MSB2-70	6,240	70	B	140	144	60	20	10	30	13	2.62
MSB2-72	6,960	72	B	144	148	60	20	10	30	13	2.76
MSB2-75	7,050	75	B	150	154	60	20	10	30	18	2.94
MSB2-76	7,120	76	B	152	156	60	20	10	30	18	3.02
MSB2-80	7,800	80	B	160	164	60	20	10	30	18	2.69

※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。



※黒染処理は施していません



形状：B

共通仕様

- 精度等級：JISN8級
(旧JIS4級)
- 歯形：並歯
- 圧力角：20°
- 材料：S45C相当


● M2.5

品番	TDK価格	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB2.5-12	1,080	12	B	30	35	23	25	12	37	10	0.16
MSB2.5-13	1,120	13	B	32.5	37.5	25	25	12	37	10	0.19
MSB2.5-14	1,170	14	B	35	40	25	25	12	37	10	0.21
MSB2.5-15	1,210	15	B	37.5	42.5	30	25	12	37	13	0.24
MSB2.5-16	1,340	16	B	40	45	32	25	12	37	13	0.28
MSB2.5-17	1,410	17	B	42.5	47.5	35	25	12	37	13	0.33
MSB2.5-18	1,580	18	B	45	50	38	25	12	37	13	0.38
MSB2.5-19	1,660	19	B	47.5	52.5	39	25	12	37	13	0.42
MSB2.5-20	1,890	20	B	50	55	40	25	12	37	13	0.46
MSB2.5-21	1,940	21	B	52.5	57.5	42	25	12	37	13	0.51
MSB2.5-22	2,120	22	B	55	60	44	25	12	37	13	0.57
MSB2.5-23	2,210	23	B	57.5	62.5	46	25	12	37	13	0.62
MSB2.5-24	2,320	24	B	60	65	48	25	12	37	13	0.68
MSB2.5-25	2,360	25	B	62.5	67.5	50	25	12	37	13	0.75
MSB2.5-26	2,500	26	B	65	70	55	25	12	37	13	0.84
MSB2.5-27	2,630	27	B	67.5	72.5	60	25	12	37	13	0.94
MSB2.5-28	2,800	28	B	70	75	60	25	12	37	13	0.99
MSB2.5-29	2,880	29	B	72.5	77.5	62	25	12	37	13	1.06
MSB2.5-30	3,060	30	B	75	80	65	25	12	37	13	1.15
MSB2.5-32	3,380	32	B	80	85	70	25	12	37	13	1.32
MSB2.5-34	3,670	34	B	85	90	70	25	12	37	13	1.44
MSB2.5-35	3,720	35	B	87.5	92.5	70	25	12	37	13	1.51
MSB2.5-36	3,890	36	B	90	95	70	25	12	37	13	1.58
MSB2.5-38	4,420	38	B	95	100	70	25	12	37	18	1.68
MSB2.5-40	4,590	40	B	100	105	70	25	12	37	18	1.83
MSB2.5-42	4,920	42	B	105	110	70	25	12	37	18	2
MSB2.5-44	5,000	44	B	110	115	70	25	12	37	18	2.16
MSB2.5-45	5,280	45	B	112.5	117.5	70	25	12	37	18	2.24
MSB2.5-46	5,720	46	B	115	120	70	25	12	37	18	2.33
MSB2.5-48	5,820	48	B	120	125	70	25	12	37	18	2.51
MSB2.5-50	6,300	50	B	125	130	70	25	12	37	18	2.7
MSB2.5-52	6,430	52	B	130	135	70	25	12	37	18	2.9
MSB2.5-54	6,920	54	B	135	140	70	25	12	37	18	3.1
MSB2.5-55	7,060	55	B	137.5	142.5	70	25	12	37	18	3.22
MSB2.5-56	7,130	56	B	140	145	70	25	12	37	18	3.32
MSB2.5-58	7,260	58	B	145	150	70	25	12	37	18	3.53
MSB2.5-60	7,780	60	B	150	155	70	25	12	37	23	3.75
MSB2.5-62	9,160	62	B	155	160	80	25	12	37	23	4.3
MSB2.5-64	9,270	64	B	160	165	80	25	12	37	23	4.54
MSB2.5-65	9,780	65	B	162.5	167.5	80	25	12	37	23	4.62
MSB2.5-66	10,080	66	B	165	170	80	25	12	37	23	4.65
MSB2.5-68	10,160	68	B	170	175	80	25	12	37	23	4.92
MSB2.5-70	10,220	70	B	175	180	80	25	12	37	23	5.1
MSB2.5-72	11,300	72	B	180	185	80	25	12	37	23	5.28
MSB2.5-75	12,470	75	B	187.5	192.5	80	25	12	37	23	5.53
MSB2.5-76	12,640	76	B	190	195	80	25	12	37	23	5.66
MSB2.5-80	13,030	80	B	200	205	80	25	12	37	23	5.22

※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。



※黒染処理は施していません



形状：B

共通仕様

- 精度等級：JISN8級
(旧JIS4級)
- 歯形：並歯
- 圧力角：20°
- 材料：S45C相当


● M3

品番	TDK価格	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB3-12	1,360	12	B	36	42	28	30	15	45	13	0.26
MSB3-13	1,510	13	B	39	45	30	30	15	45	13	0.31
MSB3-14	1,590	14	B	42	48	32	30	15	45	13	0.37
MSB3-15	1,840	15	B	45	51	36	30	15	45	13	0.44
MSB3-16	1,920	16	B	48	54	38	30	15	45	13	0.51
MSB3-17	1,970	17	B	51	57	39	30	15	45	13	0.57
MSB3-18	2,330	18	B	54	60	40	30	15	45	13	0.63
MSB3-19	2,360	19	B	57	63	45	30	15	45	13	0.74
MSB3-20	2,510	20	B	60	66	50	30	15	45	13	0.84
MSB3-21	2,750	21	B	63	69	52	30	15	45	13	0.93
MSB3-22	2,920	22	B	66	72	54	30	15	45	13	1.13
MSB3-23	3,110	23	B	69	75	56	30	15	45	13	1.18
MSB3-24	3,190	24	B	72	78	58	30	15	45	13	1.23
MSB3-25	3,440	25	B	75	81	60	30	15	45	18	1.28
MSB3-26	3,680	26	B	78	84	65	30	15	45	18	1.43
MSB3-27	3,960	27	B	81	87	65	30	15	45	18	1.51
MSB3-28	4,000	28	B	84	90	70	30	15	45	18	1.67
MSB3-29	4,050	29	B	87	93	70	30	15	45	18	1.76
MSB3-30	4,240	30	B	90	96	75	30	15	45	18	1.93
MSB3-32	4,740	32	B	96	102	75	30	15	45	18	2.13
MSB3-34	5,400	34	B	102	108	80	30	15	45	18	2.43
MSB3-35	5,450	35	B	105	111	80	30	15	45	18	2.54
MSB3-36	5,490	36	B	108	114	80	30	15	45	18	2.66
MSB3-38	6,300	38	B	114	120	80	30	15	45	23	2.84
MSB3-40	6,350	40	B	120	126	80	30	15	45	23	3.1
MSB3-42	6,960	42	B	126	132	80	30	15	45	23	3.37
MSB3-44	7,750	44	B	132	138	80	30	15	45	23	3.67
MSB3-45	7,790	45	B	135	141	80	30	15	45	23	3.82
MSB3-46	7,900	46	B	138	144	80	30	15	45	23	3.97
MSB3-48	8,900	48	B	144	150	80	30	15	45	23	4.28
MSB3-50	9,210	50	B	150	156	80	30	15	45	23	4.52
MSB3-52	9,950	52	B	156	162	80	30	15	45	23	5.18
MSB3-54	10,920	54	B	162	168	80	30	15	45	23	5.32
MSB3-55	10,990	55	B	165	171	80	30	15	45	23	5.53
MSB3-56	11,030	56	B	168	174	80	30	15	45	23	5.65
MSB3-58	12,220	58	B	174	180	80	30	15	45	23	5.85
MSB3-60	12,340	60	B	180	186	80	30	15	45	23	6.42
MSB3-62	14,060	62	B	186	192	80	30	15	45	23	6.95
MSB3-64	15,790	64	B	192	198	80	30	15	45	23	7.35
MSB3-65	15,940	65	B	195	201	80	30	15	45	23	7.81
MSB3-66	16,270	66	B	198	204	90	30	15	45	23	8.31
MSB3-68	16,980	68	B	204	210	90	30	15	45	23	8.85
MSB3-70	17,160	70	B	210	216	90	30	15	45	23	9.45
MSB3-72	18,650	72	B	216	222	90	30	15	45	23	10.03
MSB3-75	20,220	75	B	225	231	90	30	15	45	23	10.75
MSB3-76	20,390	76	B	228	234	90	30	15	45	23	11.02
MSB3-80	20,610	80	B	240	246	90	30	15	45	28	11.95

※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。



※黒染処理は施していません



形状：B

共通仕様

- 精度等級：JISN8級
(旧JIS4級)
- 歯形：並歯
- 圧力角：20°
- 材料：S45C相当


● M4

品番	TDK価格	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB4-12	2,380	12	B	48	56	35	40	20	60	18	0.58
MSB4-13	2,630	13	B	52	60	38	40	20	60	18	0.71
MSB4-14	2,880	14	B	56	64	40	40	20	60	18	0.84
MSB4-15	2,970	15	B	60	68	45	40	20	60	18	1.02
MSB4-16	3,290	16	B	64	72	50	40	20	60	18	1.19
MSB4-17	3,620	17	B	68	76	53	40	20	60	18	1.36
MSB4-18	3,970	18	B	72	80	55	40	20	60	18	1.53
MSB4-19	4,260	19	B	76	84	60	40	20	60	18	1.75
MSB4-20	4,630	20	B	80	88	65	40	20	60	18	2.01
MSB4-21	4,910	21	B	84	92	69	40	20	60	18	2.23
MSB4-22	5,260	22	B	88	96	73	40	20	60	18	2.45
MSB4-23	6,040	23	B	92	100	77	40	20	60	18	2.71
MSB4-24	6,050	24	B	96	104	80	40	20	60	18	2.94
MSB4-25	6,880	25	B	100	108	84	40	20	60	18	3.23
MSB4-26	6,990	26	B	104	112	87	40	20	60	18	3.49
MSB4-27	7,090	27	B	108	116	90	40	20	60	18	3.78
MSB4-28	7,910	28	B	112	120	95	40	20	60	18	4.11
MSB4-29	8,210	29	B	116	124	95	40	20	60	18	4.33
MSB4-30	8,680	30	B	120	128	100	40	20	60	18	4.68
MSB4-32	8,810	32	B	128	136	100	40	16	56	20	4.91
MSB4-34	9,440	34	B	136	144	100	40	16	56	20	5.43
MSB4-35	10,610	35	B	140	148	100	40	16	56	20	5.69
MSB4-36	10,680	36	B	144	152	100	40	16	56	20	5.97
MSB4-38	12,040	38	B	152	160	100	40	16	56	20	6.62
MSB4-40	13,250	40	B	160	168	100	40	16	56	23	7.1
MSB4-42	13,470	42	B	168	176	100	40	16	56	23	7.77
MSB4-44	14,820	44	B	176	184	100	40	16	56	23	8.45
MSB4-45	16,350	45	B	180	188	100	40	16	56	23	8.8
MSB4-46	16,570	46	B	184	192	100	40	16	56	23	9.16
MSB4-48	18,650	48	B	192	200	100	40	16	56	23	9.98
MSB4-50	19,060	50	B	200	208	100	40	16	56	28	10.9
MSB4-52	20,480	52	B	208	216	100	40	16	56	28	11.7
MSB4-54	22,260	54	B	216	224	100	40	16	56	28	11.8
MSB4-55	24,200	55	B	220	228	100	40	16	56	28	12.8
MSB4-56	24,340	56	B	224	232	100	40	16	56	28	13.3
MSB4-58	26,380	58	B	232	240	110	40	16	56	28	13.9
MSB4-60	27,500	60	B	240	248	110	40	16	56	28	14
MSB4-62	29,290	62	B	248	256	110	40	16	56	28	15.1
MSB4-64	31,630	64	B	256	264	110	40	16	56	28	16.3
MSB4-65	33,990	65	B	260	268	110	40	16	56	28	17.1
MSB4-66	34,080	66	B	264	272	120	40	16	56	28	17.9
MSB4-68	36,730	68	B	272	280	120	40	16	56	28	18.9
MSB4-70	37,570	70	B	280	288	120	40	16	56	28	20
MSB4-80	45,700	80	B	320	328	120	40	16	56	28	25.8

※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。



※黒染処理は施していません



形状: B

共通仕様

- 精度等級: JISN8級
(旧JIS4級)
- 歯形: 並歯
- 圧力角: 20°
- 材料: S45C相当


● M5

品番	TDK価格	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB5-12	4,090	12	B	60	70	46	50	25	75	20	1.22
MSB5-13	4,480	13	B	65	75	50	50	25	75	20	1.47
MSB5-14	4,880	14	B	70	80	52	50	25	75	20	1.72
MSB5-15	5,260	15	B	75	85	60	50	25	75	20	2.09
MSB5-16	5,750	16	B	80	90	65	50	25	75	20	2.42
MSB5-17	6,080	17	B	85	95	68	50	25	75	20	2.74
MSB5-18	7,060	18	B	90	100	70	50	25	75	20	3.05
MSB5-19	7,230	19	B	95	105	76	50	25	75	20	3.51
MSB5-20	8,130	20	B	100	110	82	50	25	75	20	3.93
MSB5-21	8,310	21	B	105	115	90	50	25	75	23	4.39
MSB5-22	9,390	22	B	110	120	95	50	25	75	23	4.86
MSB5-23	9,400	23	B	115	125	100	50	25	75	23	5.36
MSB5-24	10,430	24	B	120	130	100	50	25	75	23	5.72
MSB5-25	10,560	25	B	125	135	105	50	25	75	23	6.25
MSB5-26	11,820	26	B	130	140	110	50	25	75	23	6.82
MSB5-27	12,070	27	B	135	145	110	50	25	75	23	7.22
MSB5-28	13,640	28	B	140	150	110	50	25	75	23	7.65
MSB5-29	13,770	29	B	145	155	115	50	25	75	23	8.26
MSB5-30	15,200	30	B	150	160	120	50	25	75	23	8.9
MSB5-32	16,440	32	B	160	170	120	50	21	71	28	9.4
MSB5-34	18,480	34	B	170	180	120	50	21	71	28	10.4
MSB5-35	18,580	35	B	175	185	120	50	21	71	28	10.9
MSB5-36	20,220	36	B	180	190	120	50	21	71	28	11.8
MSB5-38	23,000	38	B	190	200	120	50	21	71	28	12.9
MSB5-40	24,700	40	B	200	210	120	50	21	71	28	13.7
MSB5-42	26,890	42	B	210	220	120	50	21	71	28	14.9
MSB5-44	29,510	44	B	220	230	120	50	21	71	28	16
MSB5-45	29,760	45	B	225	235	120	50	21	71	28	16.5
MSB5-46	31,980	46	B	230	240	120	50	21	71	28	17.6
MSB5-48	35,430	48	B	240	250	120	50	21	71	28	17.6
MSB5-50	36,870	50	B	250	260	120	50	21	71	28	18.2
MSB5-52	41,100	52	B	260	270	130	50	21	71	28	20.3
MSB5-54	44,170	54	B	270	280	130	50	21	71	28	21.4
MSB5-55	44,410	55	B	275	285	130	50	21	71	28	22.1
MSB5-56	47,480	56	B	280	290	130	50	21	71	28	22.6
MSB5-58	51,600	58	B	290	300	130	50	21	71	28	24.5
MSB5-60	54,060	60	B	300	310	130	50	21	71	28	29

※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。



※黒染処理は施していません



形状：B

共通仕様

- 精度等級：JISN8級
(旧JIS4級)
- 歯形：並歯
- 圧力角：20°
- 材料：S45C相当

● M6

品番	TDK価格	歯数	形状	基準円直径 PCD	歯先円直径 OD	ボス径 BD	歯幅 W	ボス長さ BW	ボス全長 BL	穴径 d	質量 kg
MSB6-12	6,360	12	B	72	84	55	60	28	88	23	2.12
MSB6-13	6,960	13	B	78	90	58	60	28	88	23	2.51
MSB6-14	7,470	14	B	84	96	60	60	28	88	23	2.91
MSB6-15	8,530	15	B	90	102	70	60	28	88	23	3.52
MSB6-16	9,650	16	B	96	108	75	60	28	88	23	4.06
MSB6-17	9,780	17	B	102	114	78	60	28	88	23	4.58
MSB6-18	10,980	18	B	108	120	80	60	28	88	23	5.11
MSB6-19	11,210	19	B	114	126	90	60	28	88	23	5.9
MSB6-20	12,540	20	B	120	132	100	60	28	88	23	6.74
MSB6-21	14,040	21	B	126	138	105	60	28	88	26	7.38
MSB6-22	14,270	22	B	132	144	110	60	28	88	26	8.14
MSB6-23	15,960	23	B	138	150	115	60	28	88	26	8.93
MSB6-24	16,250	24	B	144	156	120	60	28	88	26	9.76
MSB6-25	17,810	25	B	150	162	125	60	28	88	26	10.63
MSB6-26	19,500	26	B	156	168	130	60	28	88	26	11.53
MSB6-27	19,800	27	B	162	174	135	60	28	88	26	12.43
MSB6-28	22,050	28	B	168	180	140	60	28	88	26	13.44
MSB6-30	24,930	30	B	180	192	150	60	28	88	28	15.5
MSB6-32	27,530	32	B	192	204	150	60	23	83	28	16.4
MSB6-34	29,870	34	B	204	216	150	60	23	83	28	18.2
MSB6-35	36,140	35	B	210	222	150	60	23	83	28	19
MSB6-36	37,090	36	B	216	228	150	60	23	83	28	20
MSB6-38	38,200	38	B	228	240	150	60	23	83	28	22
MSB6-40	43,810	40	B	240	252	150	60	23	83	28	24
MSB6-42	46,230	42	B	252	264	150	60	23	83	38	26
MSB6-44	51,650	44	B	264	276	150	60	23	83	38	28.3
MSB6-45	52,280	45	B	270	282	180	60	23	83	38	30.7
MSB6-46	55,350	46	B	276	288	180	60	23	83	38	32.1
MSB6-48	59,990	48	B	288	300	180	60	23	83	38	34.5
MSB6-50	63,110	50	B	300	312	180	60	23	83	38	37.2

※ご要望に応じた、軸穴加工、キー加工、止めねじ加工を承ります。別途、お問い合わせください。